

Powr-Grip® mounting cups provide a reliable, temporary fastener on almost any smooth, nonporous surface, such as metal or glass. Available in a range of styles to cover most applications and capacity requirements, they can be used to mount cameras, scopes, testing equipment, antennas, lights, signs, and much more. Mounting cups employ a threaded stud, female insert or tie-down bail to fasten accessories and equipment to the cup. They attach to either flat or curved surfaces, including filing cabinets, desks, automobiles, boats and recreational vehicles. Since mounting cups attach and release in seconds, they can be moved quickly from one place to another, without damaging most surfaces. Studs are available in various lengths and threads, including metric sizes.

An important safety feature of every Powr-Grip mounting cup is the red-line vacuum indicator: When the cup is fully evacuated and ready for use, the plunger stays in and the line is not visible. Should the line reappear, a check valve allows the operator to repump the cup without loss of remaining vacuum. A firm push or pull on the release tab at the edge of the rubber pad releases all types of mounting cups except the N6000NBP, which employs a finger-operated release valve.



LJ45PHC (CLEAT)

Specifications:
 Model: LJ45PHC
 Mount: Black Polycarbonate
 Head: 2 knob control
 Stud: 1/4-20
 Concave Pad: 4.5" [115 mm], (LJ45)
 Radius: 12" [305 mm]
 Capacity: 10 lbs. [5 kg.]
 Includes pad protector.



TL6PH3025 (GRIPPER)

Specifications:
 Model: TL6PH3025
 Mount: Black Aluminum
 Head: 3 knob control
 Stud: 1/4-20
 Concave Pad: 6" [153 mm], (TL6)
 Radius: 12" [305 mm]
 Capacity: 6.7 lbs. [3039 g.]
 Includes pad protector.



LJ45PH155 (NUKLEHEAD JUNIOR)

Specifications:
 Model: LJ45PH155
 Mount: Black Aluminum
 Head: Double ball joint
 Concave Pad: 4 1/2" [115 mm], (LJ45)
 Radius: 12" [305 mm]
 Capacity: 8.9 lbs. [4 kg.]
 Includes pad protector.



TL6PH155 (NUKLEHEAD)

Specifications:
 Model: TL6PH155
 Mount: Black Aluminum
 Head: Double ball joint
 Concave Pad: 6" [153 mm], (TL6)
 Radius: 12" [305 mm]
 Capacity: 8.9 lbs. [4 kg.]
 Includes pad protector.



N6000BP

Specifications:
 Model: N6000BP
 Mount: 1/4" Silver Aluminum Plate
 Tapped: 1/4-20 and 3/8-16
 Concave Pad: 10" [254 mm], (G0750)
 Radius: 13" [330 mm]
 Capacity: 175 lbs. [79 kg.]
 Includes pad protector.



TL6TD (TIE-DOWN)

Specifications:
 Model: TL6TD
 Mount: Silver Aluminum
 Bail: Steel
 Concave Pad: 6" [153 mm], (TL6)
 Radius: 12" [305 mm]
 Capacity: 70 lbs. [32 kg.]
 Includes pad protector.



TL3AMB

Specifications:
 Model: TL3AMB1420T38L
 Mount: Black Metal
 Stud: 1/4-20 x 3/8"
 Concave Pad: 3" [77 mm], (TL3)
 Radius: 4" [102 mm]
 Capacity: 15 lbs. [7 kg.]
 Includes pad protector.
 Other stud lengths available.



LJ45AMP

Specifications:
 Model: LJ45AMP1420T38L
 Mount: Black Polycarbonate
 Stud: 1/4-20 x 3/8"
 Concave Pad: 4.5" [115 mm], (LJ45)
 Radius: 12" [305 mm]
 Capacity: 40 lbs. [18 kg.]
 Includes pad protector.
 Other stud lengths available.



LJ45AMC

Specifications:
 Model: LJ45AMC1420T
 Mount: Black Polycarbonate
 Thread: 1/4-20
 Concave Pad: 4.5" [115 mm], (LJ45)
 Radius: 12" [305 mm]
 Capacity: 40 lbs. [18 kg.]
 Includes pad protector.



TL6AMB

Specifications:
 Model: TL6AMB1420T14L
 Mount: Black Aluminum
 Stud: 1/4-20 x 1/4"
 Concave Pad: 6" [153 mm], (TL6)
 Radius: 12" [305 mm]
 Capacity: 70 lbs. [32 kg.]
 Includes pad protector.
 Other stud lengths available.

ACCESSORIES



AS375 & AS625 • Light Studs - Use with Cleat, Gripper, Nukklehead or other mounting cups to mount photographic lights on almost any smooth, nonporous surface. Available in 3/8" [9.5 mm] diameter by 2" [51 mm] length (AS375) or 5/8" [16 mm] diameter by 3" [76 mm] length (AS625), to fit on a 1/4-20 threaded stud.



TLT • T-Handle - Use with most mounting cups to aid in the placement and positioning of small loads. 2-3/8" [60 mm] width by 1-1/4" [32 mm] height handle, to fit on most 1/4-20 studs.

Conversion Bushing - Converts 1/4-20 (U.S.) thread to 3/8-16 (European) thread.